



STRAIGHT SHANK DRILLS

RECOMMENDED CUTTING CONDITIONS EMPFOHLENE SCHNEIDPARAMETER

DQ505 SERIES

HSS-E, DH100 WORM PATTERN DRILLS

VC = M/MIN
RPM = rev./min.
FEED = mm/rev.

ISO	VDI 3323	Material Description	Vc	Parameter	Drill Diameter (mm)										
					2.0	3.0	4.0	6.0	8.0	10.0	13.0	16.0	18.0	20.0	30.0
P	1	Non-alloy steel	30	RPM	4770	3180	2390	1590	1190	950	730	600	530	480	320
				FEED	0.02~0.04	0.03~0.05	0.04~0.06	0.05~0.08	0.10~0.13	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
			25	RPM	3980	2650	1990	1330	990	800	610	500	440	400	270
				FEED	0.02~0.04	0.03~0.05	0.04~0.06	0.05~0.08	0.10~0.13	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
	20		RPM	3180	2120	1590	1060	800	640	490	400	350	320	210	
			FEED	0.02~0.04	0.03~0.05	0.04~0.06	0.05~0.08	0.10~0.13	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28	
	20		RPM	3180	2120	1590	1060	800	640	490	400	350	320	210	
			FEED	0.01~0.02	0.01~0.03	0.02~0.04	0.02~0.05	0.03~0.06	0.03~0.06	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18	
	6	Low alloy steel	25	RPM	3980	2650	1990	1330	990	800	610	500	440	400	270
				FEED	0.02~0.04	0.03~0.05	0.04~0.06	0.05~0.08	0.10~0.13	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.2	0.19~0.25	0.22~0.28
20			RPM	3180	2120	1590	1060	800	640	490	400	350	320	210	
			FEED	0.02~0.04	0.03~0.05	0.04~0.06	0.05~0.08	0.10~0.13	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.2	0.19~0.25	0.22~0.28	
20	RPM		3180	2120	1590	1060	800	640	490	400	350	320	210		
	FEED		0.01~0.02	0.01~0.03	0.02~0.04	0.02~0.05	0.03~0.06	0.03~0.06	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18		
10	High alloyed steel, and tool steel		15	RPM	2390	1590	1190	800	600	480	370	300	270	240	160
				FEED	0.02~0.04	0.03~0.05	0.04~0.06	0.05~0.08	0.10~0.13	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
30		RPM	4770	3180	2390	1590	1190	950	730	600	530	480	320		
		FEED	0.02~0.04	0.03~0.05	0.04~0.06	0.05~0.08	0.10~0.13	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28		
25		RPM	3980	2650	1990	1330	990	800	610	500	440	400	270		
		FEED	0.01~0.02	0.01~0.03	0.02~0.04	0.02~0.05	0.03~0.06	0.03~0.06	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18		
30		Nodular cast iron	30	RPM	4770	3180	2390	1590	1190	950	730	600	530	480	320
				FEED	0.02~0.04	0.03~0.05	0.04~0.06	0.05~0.08	0.10~0.13	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
20	RPM		3180	2120	1590	1060	800	640	490	400	350	320	210		
	FEED		0.01~0.02	0.01~0.03	0.02~0.04	0.02~0.05	0.03~0.06	0.03~0.06	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18		
25	Malleable cast iron		25	RPM	3980	2650	1990	1330	990	800	610	500	440	400	270
				FEED	0.02~0.04	0.03~0.05	0.04~0.06	0.05~0.08	0.10~0.13	0.11~0.15	0.11~0.17	0.12~0.18	0.14~0.20	0.19~0.25	0.22~0.28
20			RPM	3180	2120	1590	1060	800	640	490	400	350	320	210	
			FEED	0.01~0.02	0.01~0.03	0.02~0.04	0.02~0.05	0.03~0.06	0.03~0.06	0.04~0.10	0.06~0.12	0.08~0.14	0.10~0.16	0.12~0.18	